

THE B&G DROP REVOLUTION

HOT MOBILE PRESSURE WASHER

KEY SPECIFICATION

- 11ltr/min Water Flow,
- 120bar/1740psi Pressure
- High Quality Annovi Reverberi Pump
- High Pressure Chemical System
- Automatic Stop/Start Safety System



MAC18/RA

Water Flow	11lt/min
Pressure	120bar, 1740psi
Motor Specification	3hp, 1450rpm
Chemical	High Pressure
Shutdown System	Auto Stop/Start
Temperature	0-100°C
Power	240v
Weight	90kg
Dimensions (h x w x d)	86 x 60 x 90cm

HIGH QUALITY ANNOVI
REVERBERI RC 11.17 PUMP

STANDARD FEATURES

- Tough GRP plastic chassis and cover
- Efficient M1 boiler system with double spiral coil
- 4 large robust wheels for tough terrain
- High pressure detergent system
- 7lt Internal detergent tank
- 22lt Internal fuel tank
- Stainless steel water header tank with type AB airgap
- High quality Annovi Reverberi RC 11.17 pump
- Industrial 1450rpm low revving 4 pole Nicolini motor
- Automatic Stop/Start safety system
- Bypass valve and safety valve
- Burner control with pressure switch and thermostat
- Pressure gauge
- Including 10mt high pressure hose, single lance and heavy duty trigger

THE B&G ATOM XL

COLD MOBILE PRESSURE WASHER

KEY SPECIFICATION

- Stainless Steel Cover with Steel Chassis
- High Quality Annovi Reverberi Pump
- Low Revving 1450rpm Industrial Motor
- Automatic Stop/Start Safety System



MAC154

MAC155

Water Flow	11lt/min	15lt/min
Pressure	120bar, 1740psi	150bar, 2200psi
Motor Specification	3hp, 1450rpm	5.5hp, 1450rpm
Chemical	High Pressure	High Pressure
Shutdown System	Auto Stop/Start	Auto Stop/Start
Power	240v	415v
Weight	70kg	80kg
Dimensions (h x w x d)	95 x 50 x 80cm	95 x 50 x 80cm

STANDARD FEATURES

- Painted steel chassis
- Stainless steel cover
- Automatic Stop/Start safety system
- 2 large robust wheels for tough terrain
- High pressure chemical system
- Reliable Annovi Reverberi pump
- Industrial 1450rpm 4 pole electric Nicolini motor
- Bypass valve
- Current thermal overload protection
- Including 10mt high pressure hose, single lance with swash nozzle and heavy-duty trigger

**BYPASS VERSIONS ALSO AVAILABLE IN 240v
OR 415v WITH LOW PRESSURE CHEMICAL**