

THE B&G PLANTMASTER HOT STATIC PRESSURE WASHER

KEY SPECIFICATION

- 12ltr, 15ltr or 21ltr/min Water Flow
- 100bar/1500psi or 200bar/3000psi Pressure
- High Efficiency M2 Boiler System
- Automatic Stop/Start Safety System
- High Quality Painted Steel Cabinet

STANDARD FEATURES

- Full frost protection and cabinet lagging
- High Efficiency M2 boiler system
- Double spiral M2 coil
- Automatic stop/start system
- High pressure chemical system
- Professional interpump with ceramic pistons
- Industrial 1450rpm 4 pole electric Nicolini motor
- Flame failure and leak detection system
- 16lt fuel tank with low level sensor
- Burner control with flow switch and thermostat
- 24v low tension safety controls
- Mains power on lamp

CABINET FINISH

- Powder coated steel cabinet with lockable controls
- High quality matte paint finish
- Lockable powder coated steel front door
- Zinc phosphate steel pre-treatment for weather proofing



UPGRADE TO THE FULL STAINLESS STEEL PLANTMASTER S.S.



HIGH EFFICIENCY BOILER WITH
INCREASED WATER TEMPERATURE AND
REDUCED FUEL COSTS & EMISSIONS

	PLANTMASTER1	PLANTMASTER2	PLANTMASTER4
Water Flow	12lt/min	15lt/min	21lt/min
Pressure	100bar, 1500psi	200bar, 3000psi	200bar, 3000psi
Motor Specification	3hp, 1450rpm	7.5hp, 1450rpm	10hp, 1450rpm
Chemical	High Pressure	High Pressure	High Pressure
Shutdown System	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start
Temperature	0-100°C	0-100°C	0-100°C
Power	240v	415v	415v
Weight	230kg	250kg	270kg
Dimensions (h x w x d)	160 x 82 x 56cm	160 x 82 x 56cm	160 x 82 x 56cm