



food



transport



hire



public sectors



industry

EDGE



A24

- More than 90/120 Kg. of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Compact size • Stability even when fully loaded • Front independent wheel-drive with tight steering radius
- Easy access to electrical components
- Detergent dispenser
- Automatic device for squeegee lifting while reversing
- Automatic device that stops brushes and detergent supply when the machine is standing still
- Antifoam device
- Self-levelling brushes

- High-performance batteries resulting in highworking efficiency • no. of battery and max. capacity (optional): M1x36V/420Ah C5 1200 cycles (cassone)

A24



scrubber driers

| | A 24 6000 | A 24 7100 |
|--------------------------------|---------------------------------|---------------------------------|
| Code | 6404 | 6405 |
| Power supply | 36V | 36V |
| scrubbing / squeegee width | 870 / 1110 mm | 1020 / 1250 mm |
| max speed/working capacity | 7 km/h - 6090 m ² /h | 7 km/h - 7140 m ² /h |
| detergent tank capacity | 200 l / 52,84 gal | 200 l / 52,84 gal |
| recovery tank capacity | 210-240 l/55,5-63,4 gal | 210-240 l/55,5-63,4 gal |
| traction motor | front wheel / 900W | front wheel / 900W |
| RPM/ pressure on the brushes | 150-90 kg /198 lbs | 150-120 kg /264 lbs |
| brush motor power | 1500W | 1500W |
| max gradient empty / full tank | 10 / 8% | 10 / 8% |
| depression/ vacuum motor | 1800 mmH ₂ O/ 600W | 1800 mmH ₂ O/ 600W |
| dimensions / weight | 190x96x145cm/ 345kg | 190x112x145cm/ 375kg |

