

Hose, Hose Clips & Sealant



Garden Hose	160
Extra Flex Hose	160
Layflat Hose	160
Kanaflex Hose	160
Reinforced Hose	160
Diesel Transfer Hose	160
Spiral Hose	160
Food Grade Hose	160
High Pressure Hose	161
High Pressure Connection Hoses	161
Stainless Steel Hose Clamps	162
Stainless Steel Hose Clips	162
Zinc Plated Hose Clips	162
O Clip Pliers	162
Loctite® & Sealant	162

Low Pressure Hose

Extra Flex PVC - 25 metre coil



Part No.	id	Bar
GH1225Y	1/2"	10
GH1625Y	5/8"	10
GH1925Y	3/4"	8
GH2525Y	1"	6

- Temp -15°C to 60°C

Extra Flex PVC - sold by the metre



Part No.	id	Bar
GH12Y	1/2"	10
GH16Y	5/8"	10
GH19Y	3/4"	8
GH25Y	1"	6

- Temp -15°C to 60°C
- Complete roll 50 metres

PVC Garden 1/2" - 15 or 30 metre coil



Part No.	Coil	Bar
LGL1215	15M	8
LGL1230	30M	8

- Temp -15°C to 60°C

Layflat - sold by the metre



Part No.	id	Bar
P16LFB	1"	7
P20LFB	1 1/4"	7
P24LFB	1 1/2"	5
P32LFB	2"	4.5
P48LFB	3"	4

- Temp -25°C to 60°C
- Complete roll 100 metres

Clear Reinforced PVC - sold by the metre



Part No.	id	Bar
01-06	1/4"	16
01-516	5/16"	16
01-10	3/8"	15
01-12	1/2"	15
01-16	5/8"	12
01-19	3/4"	10
01-25	1"	10

- Temp -15°C to 60°C
- Complete roll 30 metres

Clear PVC - sold by the metre



Part No.	id
503-1008	8mm
503-1010	1/2"
503-1012	3/4"
503-1014	1 1/2"

- Temp -15°C to 60°C
- Complete roll 30 metres

Clear Wire Reinforced PVC - sold by the metre



Part No.	id	Bar
503-1001	19mm	9
503-1000	25mm	8

- Temp -25°C to 65°C
- Complete roll 30 metres

Kanaflex - sold by the metre



Part No.	id	Bar
12-CD07	3/4"	6
12-CD10	1"	5.5
12-CD12	1 1/4"	5.1
12-CD15	1 1/2"	4.3
12-CD20	2"	3.8
12-CD30	3"	2.5

- Temp -15°C to 65°C
- Complete roll 30 metres

Diesel Delivery - sold by the metre



Part No.	id	Bar
DDH025	1"	7

- Temp -15°C to 60°C
- U.V. & ozone resistance
- Manufactured in rubber PVC alloy
- Complete roll 30 metres

Diesel Suction - sold by the metre



Part No.	id
DSH025	1"

- Reinforced PVC/Nylon
- Temp -15°C to 65°C
- U.V. & ozone resistance
- Complete roll 30 metres

10 Metre - Spiral with Fittings



Part No.
8000-7204

- Adjustable nozzle
- Quick release couplings
- Non-return check valve
- 10 Metre x 12 mm Ø

Food Grade - Non Scuff



Part No.
503-1020

- 1/2" Ø x 20 Metre
- Temp -20°C - 90°C
- Max press 25 Bar
- 1x 1/2" BSPM QR adaptor
- 1x 3/4" BSPF QR adaptor

High Pressure Hose

1/4" id - 160 or 210 Bar

1/4" F x M22 F fittings

Part No.	Length	Bar	Description	Temp
TUBIN16	16M	160	1/4" id plastic coated hose	60°C
TUBIN8R	8M	210	1/4" id 1 wire rubber hose	150°C



3/8" id - 210 or 400 Bar

3/8" F x 3/8" M fittings

Part No.	Length	Bar	Description	Temp
HP2600	10M	210	3/8" id 1 wire rubber hose	150°C
HP2600-20	20M	210		
HP2600-40	40M	210		
HP4800	10M	400	3/8" id 2 wire rubber hose	150°C
HP4800-20	20M	400		
HP4800-40	40M	400		



3/8" M x M22 F fittings

Part No.	Length	Bar	Description	Temp
HP2600K	10M	210	3/8" id 1 wire rubber hose	150°C
HP4800K	10M	400	3/8" id 2 wire rubber hose	150°C



M22 F x M22 F fittings

Part No.	Length	Bar	Description	Temp
HP2600KK	10M	210	3/8" id 1 wire rubber hose	150°C
HP2600KK-25	25M	210		
HP2600KK-50	50M	210		
HP4800KK	10M	400	3/8" id 2 wire rubber hose	150°C
HP4800KK-15	15M	400		
HP4800KK-30	30M	400		



High Pressure Connection Hoses

Part No.	Description	Length	Inlet	Outlet	Bar	Temp
BP1	3/8" id 1 wire rubber hose	330mm	3/8" F 90°	3/8" F	210	150°C
BP2		355mm	3/8" F	3/8" F		
399-1025	3/8" id 2 wire rubber hose	250mm	3/8" F	3/8" F	400	150°C
399-1021		590mm	3/8" F 45°	3/8" F		
503-1025		870mm	3/8" F 45°	3/8" F 90°		
399-1023		1180mm	3/8" F 90°	3/8" F 90°		
503-1022		1730mm	3/8" F 90°	3/8" F 90°		



3/8"
F



45°



90°

Hose Clips & Sealant

Hose Clips - Zinc Plated



Part No.	Size	Adjustment
502-1000	12	8 - 12 mm
502-1001	16	10 - 16 mm
502-1003	20	12 - 22 mm
502-1004	22	16 - 27 mm
502-1005	30	20 - 32 mm
502-1006	35	25 - 40 mm
502-1007	50	35 - 50 mm
502-1008	55	40 - 60 mm
502-1009	70	50 - 70 mm
502-1010	90	70 - 90 mm

- Zinc plated mild steel worm drive to BS5315

Hose Clips - Stainless Steel



Part No.	Adjustment
502-1020	8 - 16 mm
502-1021	12 - 20 mm
502-1022	16 - 25 mm
502-1023	20 - 32 mm
502-1024	25 - 40 mm
502-1025	32 - 50 mm
502-1026	40 - 60 mm
502-1027	50 - 70 mm
502-1028	60 - 80 mm
502-1029	70 - 90 mm

- 301 S/Steel for the band & housing
- 305 S/Steel for the screw
- Band width is 1/2"

Hose Clips - Stainless Steel



Part No.	Adjustment
502-1060	43 - 47 mm
502-1061	47 - 51 mm
502-1063	51 - 55 mm
502-1072	55 - 59 mm
502-1064	59 - 63 mm
502-1065	63 - 68 mm
502-1066	68 - 73 mm
502-1067	73 - 79 mm
502-1071	79 - 85 mm
502-1068	85 - 91 mm
502-1069	91 - 97 mm
502-1070	104 - 112 mm

- S/Steel band - zinc plated screws
- Designed for 360° clamping
- High torque applications
- Nylon lock feature

O Clips - Zinc Plated



Part No.	Size
502-1100	11 - 13mm
502-1101	15 - 18mm
502-1104	20 - 23mm
502-1102	23 - 27mm

- Zinc plated mild steel

O Clip Pliers



Part No.
800-1005

Teflon Tape



Part No.	Length	Width
9902-1252	13.2m	12mm

Loctite® 55 - Pipe Sealing Cord



Part No.	Size
483283	50m

- Temperatures -50°C to 130°C
- Non curing, immediate, full pressure seal
- Allows fittings to be 'Backed Off' for alignment
- UK & European approved for drinking water
- CORGI approved
- Seals against hot or cold water & gases

Pipe Joint Sealant



Part No.	Size
9902-25551	8oz can

- Easy to apply
- Non-hardening - non-toxic
- Brush top applicator

Loctite® Threadlocker



Part No.	Description	Size
1335885	243 medium strength threadlock	50ml
234853	2701 high strength threadlock	50ml

- Temperatures -55°C to 150°C
- Suitable for all metal fasteners, including stainless steel as well as coated ones, e.g. zinc-coated
- Ideal for locking studs on engine blocks and pump housings

Loctite® 5331 RTV Plastic Pipe Sealant



Part No.	Size
142492	100ml

- Temperatures -50°C to 150°C
- Ideal for use on threaded plastic or plastic/metal fittings