

Swivels



In-Line Brass & Stainless Steel Swivels

176 - 177

90° Brass & Stainless Steel Swivels

177

Polypropylene Swivels

177

High Pressure Rotating Heads

177

Mosmatic Swivels

178

Mosmatic Bulk Head Swivels

178

Swivels

LR Series Brass Swivels



Part No.	Threads
26.1000.00	3/8" M x 3/8" F
26.1000.05	3/8" M x 1/4" F

- Max press 220 Bar
- Max flow 30 Lpm
- Max temp 90°C
- Buna seals



Male x Male thread Brass Swivels



Part No.	Threads
4100801005	3/8" M x 3/8" M
4100801006	3/8" M x 1/4" M
4100801007	3/8" M x M22 M

- Max press 220 Bar
- Max flow 30 Lpm
- Max temp 150°C
- Viton seals



High Pressure Brass Swivels



Part No.	Threads
371702	3/8" M x 3/8" F
371704	3/8" M x M22 M

- Max press 280 Bar
- Max flow 30 Lpm
- Max temp 150°C
- Viton seals



High Pressure S/Steel Swivel



Part No.	Threads
371700	3/8" M x 3/8" F

- Max press 280 Bar
- Max flow 30 Lpm
- Max temp 150°C
- Viton seals



MR-0 Series Brass Swivels



Part No.	Threads
26.1040.00	1/4" M x 1/4" F
26.1050.00	3/8" M x 3/8" F
26.1055.00	1/2" M x 1/2" F

- Max press 250 Bar
- Max flow 40 Lpm
- Max temp 160°C
- Viton seals

MR-1 Series S/Steel Swivels



Part No.	Threads
26.1060.00	1/4" M x 1/4" F
26.1061.00	3/8" M x 3/8" F

- Max press 350 Bar
- Max flow 40 Lpm
- Max temp 160°C
- Viton seals



SW600 - S/Steel Swivel



Part No.	Threads
30.5840.00	3/8" F x 3/8" M

- Max press 600 Bar
- Max flow 60 Lpm
- Max temp 100°C
- 30 Rpm max speed
- NBR (buna) seals



SW5 Series S/Steel or Brass Swivel



Part No.	Threads	Material
26.1070.00	1/2" M x 1/2" F	S/Steel
26.1080.00	1/2" M x 1/2" F	Brass

- Max press 200 Bar
- Max flow 160 Lpm
- Max temp 160°C
- Viton o-rings



SWIF Series S/Steel Swivels

Part No.	Threads
SWIFMF1	1/2" M x 1/2" F

- Max press 30 Bar
- Max flow 40 Lpm
- Max temp 95°C
- Viton seals
- Ball bearing swivel



SW65 - Large Flow Brass Swivel

Part No.	Threads
30.6480.00	1/2" M x 1/2" F

- Max press 24 Bar
- Max flow 100 Lpm
- Max temp 100°C
- Viton & Buna seals
- Ball bearing swivel

Swivels & Rotating Heads

990 Series 90° Brass Swivels

Part No.	Threads
990-6F6F-B	3/8" F x 3/8" F
990-6F6M-B	3/8" F x 3/8" M



- Max press 100 Bar
- Brass construction
- Max temp 80°C
- Buna N seals

SW90 - Brass & S/Steel

Part No.	Threads	Bar	Lpm
26.1300.20	1/4" M x 1/4" F	250	40
26.1300.40	3/8" M x 3/8" F	250	40
26.1320.00	1/2" M x 1/2" F	350	80



- Max flow 80 Lpm - Max press 350 Bar
- Max temp 160°C
- Teflon & Viton seals
- S/Steel bolt & nickel plated brass body
- 26.1320.00 complete s/steel body

Stainless Steel Hose Tail Swivels

Part No.	Thread x Barb
SWIFB13	1/2" M x 13mm
SWIFB16	1/2" M x 16mm
SWIFB19	1/2" M x 19mm



- Max press 40 Bar
- 316 stainless steel
- Max temp 95°C
- Viton seals

Polypropylene Swivels

Part No.	Threads
9901-SW100	1" F x 1" M
9901-SW150	1 1/2" F x 1 1/2" M
9901-SW200	2" F x 2" M



- Max press 5 Bar
- Teflon thrust bearing
- Viton seals
- Stainless steel drive stud

GR38 High Pressure Rotating Head

Part No.	Max Bar	Max Lpm	Dimensions
26.1400.00	350	40	36mm Ø x 115mm long

- 3/8" BSPM inlet
 - 2 x M12 F outlets
 - Max working temp 90°C
 - Nickel plated brass body
 - Viton seals
- Can also be fitted with 1/8" central nozzle. Fitted with blanking plug as standard



URF180 High Pressure Rotating Head

Part No.	Max Bar	Max Lpm	Dimensions
25.1130.00	250	30	35mm Ø x 65mm long

- 1/4" NPTM inlet
- 2 x 1/8" BSPF outlets
- Anti-wear s/steel pin
- Brass body
- Max working temp 80°C



URF400 High Pressure Rotating Head

Part No.	Max Bar	Max Lpm	Dimensions
25.1170.00	350	80	44mm Ø x 88mm long

- 1/2" BSPF inlet
- 2 x 1/4" BSPF outlets
- Anti-wear s/steel pin
- Brass body
- Max working temp 80°C



WAW High Pressure Rotating Head

Part No.	Max Bar	Max Lpm
85.790.006	276	30
Dimensions 88mm Ø x 154mm long		
See page 181 for inlet adaptors		



- 1/4" F taper inlet
- 1/4" NPTF outlet
- Max working temp 80°C
- Fitted with grease nipple

Mounting Bracket

Part No.	Description
85.791.001	Bracket for rotary head 4 x 8mm mounting holes 107mm Ø

- Use with WAW rotating head



Mosmatic Swivels

Mosmatic Heavy Duty Swivels

- Max press 275 Bar
- Max temp 120°C
- Max speed 30 Rpm
- Nickel plated brass body
- Triple bearing system
- Stainless steel bearings
- Multiple seal system
- Totally corrosion resistant
- For water, oil, air, pH 3-12

DGL - Triple Bearing Female x Male Thread



Part No.	Female	Male
31.001	1/4" BSP	1/4" BSP
31.003	1/4" BSP	3/8" BSP
31.101	3/8" BSP	1/4" BSP
31.103	3/8" BSP	3/8" BSP

DGL - Triple Bearing Female Thread



Part No.	Female	Female
31.002	1/4" BSP	1/4" BSP
31.004	1/4" BSP	3/8" BSP
31.104	3/8" BSP	3/8" BSP

DGS - Dual Bearing Female x Male Thread



Part No.	Female	Male
30.001	1/4" BSP	1/4" BSP
30.003	1/4" BSP	3/8" BSP
30.101	3/8" BSP	1/4" BSP
30.103	3/8" BSP	3/8" BSP

DGK Single Bearing Hose Barb x Thread



Part No.	Thread	Barb
32.031	1/4" BSP	6mm
32.032	1/4" BSP	8mm
32.039	1/4" BSP	10mm
32.131	3/8" BSP	6mm
32.132	3/8" BSP	8mm
32.139	3/8" BSP	10mm



WDG - Triple Bearing 90° Swivels

Part No.	Female Thread	Male Thread	Dimension (A)
40.009*	1/4" BSPF	1/4" BSPM Parallel	7mm ID
40.013	3/8" BSPF	3/8" BSPM Tapered	7mm ID
40.112	3/8" BSPF	3/8" BSPM Parallel	10mm ID

- Max press 150 Bar
- Max temp 90°C
- Max speed 30 Rpm
- Nickel plated brass body
- Stainless steel bearings
- Multiple seal system
- Totally corrosion resistant
- Easy turning at high pressure
- For water, oil, air, pH 3-12
- * Without snap ring

Mosmatic DGG - DGF Triple Heavy Duty Bulkhead Swivels

- Max press 275 Bar
- Max temp 120°C
- Max speed 30 Rpm
- Nickel plated brass body
- Triple bearing system
- Stainless steel bearings
- Multiple seal system
- Totally corrosion resistant
- For water, oil, air, pH 3-12

M22 Male x Male thread



Part No.	Male	Male
33.253	M22 x 1.5 M	3/8" BSP

Female thread x Male thread



Part No.	Female	Male
33.001	1/4" BSP	1/4" BSP
33.003	1/4" BSP	3/8" BSP
33.101	3/8" BSP	1/4" BSP
33.103	3/8" BSP	3/8" BSP

Flanged F thread x M thread



Part No.	Female	Male
35.103	3/8" BSP	3/8" BSP

90° M22 Male x Male thread



Part No.	Male	Male
33.553	M22 x 1.5 M	3/8" BSP