

Fronius Battery Charger

Charger for lead acid batteries



- Lightweight portable battery chargers
- Energy efficient and can extend battery life
- Charge different batteries with one charger
- Battery charge level indicator

Fronius Selectiva battery charging systems use intelligent technology to charge a range of different batteries, recognising the age and charge level, to deliver the correct amount of current. This minimises warming, to prolong the life of the battery and reduce maintenance.

These lightweight chargers can be installed in fixed positions or used as portable charging devices for different machines.

Features include:

- Automatic detection of battery voltage
- LED indicator light to show when the battery is fully charged and ready to use
- Facility for scheduled charging, e.g. overnight or to co-ordinate with shift patterns
- Rapid charging function

The models we typically supply to our customers, e.g. for charging scrubber dryers and floor sweepers, are the Selectiva 1kW, Selectiva 4.0 2kW and Selectiva 4.0 3kW, although a wide range of options is available, so for larger chargers or complete charging systems, please give us a call.

Technical Data: Fronius Battery Chargers

SELECTIVA 1kW

Type: 1kW

Dimensions W/H/D: 247 x 162 x 88 mm

Weight including charging and mains leads: 4 kg

Protection class: IP40

Mains lead: 2 m

Charging lead: 2,5 m

Mains voltage: 1 x 230V AC

(-15%/+15%)

BATTERY VOLTAGE	DEVICES	OUTPUT		PHASES	MAINS			
	DESIGNATION	VOLTAGE	CURRENT		VOLTAGE	CURRENT	POWER	FUSE
12V	Selectiva 1020	12	20	1	230V	3A	0,3kW	16A
	Selectiva 1030	12	30	1	230V	3A	0,4kW	16A
24V	Selectiva 2010	24	10	1	230V	3A	0,3kW	16A
	Selectiva 2015	24	15	1	230V	3A	0,4kW	16A
	Selectiva 2020	24	20	1	230V	4A	0,7kW	16A
	Selectiva 2032	24	32	1	230V	8A	1,0kW	16A
	Selectiva 2040	24	35	1	230V	8A	1,1kW	16A

SELECTIVA 4.0 2kW

Type: 2kW

Dimensions W/H/D: 341 x 198 x 110 mm

Weight including charging and mains leads: 6 kg

Protection class: IP21

Mains lead: 2,5 m

Charging lead: 3 m

Mains voltage: 1 x 230V AC

(-15%/+15%)

BATTERY VOLTAGE	DEVICES	OUTPUT		PHASES	MAINS			
	DESIGNATION	VOLTAGE	CURRENT		VOLTAGE	CURRENT	POWER	FUSE
24V	Selectiva 4.0 2040 2kW	24	40	1	230V	8A	1,5kW	16A
	Selectiva 4.0 2050 2kW	24	50	1	230V	10A	1,9kW	16A
	Selectiva 4.0 2060 2kW	24	60	1	230V	12A	2,3kW	16A
	Selectiva 4.0 2070 2kW	24	70	1	230V	12A	2,4kW	16A
36/48V	Selectiva 4.0 4020 2kW	24	20	1	230V	8A	1,5kW	16A
	Selectiva 4.0 4035 2kW	24	35	1	230V	12A	2,3kW	16A

SELECTIVA 4.0 3kW

Type: 3kW

Dimensions W/H/D: 417 x 198 x 110 mm

Weight including charging and mains leads: 8 kg

Protection class: IP21

Mains lead: 2,5 m

Charging lead: 3 m

Mains voltage: 1 x 230V AC

(-15%/+15%)

BATTERY VOLTAGE	DEVICES	OUTPUT		PHASES	MAINS			
	DESIGNATION	VOLTAGE	CURRENT		VOLTAGE	CURRENT	POWER	FUSE
24V	Selectiva 4.0 2080 3kW	24	80	1	230V	15A	2,8kW	16A
	Selectiva 4.0 2100 3kW	24	100	1	230V	15A	3,0kW	16A
	Selectiva 4.0 2120 3kW	24	120	1	230V	16A	3,0kW	16A
36/48V	Selectiva 4.0 4045 3kW	48	45	1	230V	15A	3,0kW	16A
	Selectiva 4.0 4060 3kW	48	60	1	230V	15A	3,0kW	16A

See this product on our website <https://www.bgclean.co.uk/product/fronius-battery-charger/>

Call us FREE on 0808 301 4577

For advice and best prices on cleaning equipment to buy, lease or hire.

B&G
CLEANING SYSTEMS LTD

www.bgclean.co.uk