

# Pressure Gauges



2" Gauge.....	276
2 1/2" Gauges.....	276
4" Gauges.....	276
6" Gauge.....	276
Rubber Case for 2 1/2" Gauges.....	276
Gauge Isolator.....	276

Available from B&G Cleaning Systems  
Call 0808 163 7983

# Pressure Gauges

- Glycerine filled
- Stainless steel cases
- Brass & copper alloy wetted parts
- Bottom or rear entry versions
- 2", 2 1/2", 4" & 6" faces
- Accurate to  $\pm 1.6\%$

## 2 1/2" Face - 1/4" M Thread

Bottom Entry



**WIKAI**

Part No.	Bar
GG2SB4	0-4
GG2SB6	0-6
GG2SB10	0-10
GG2SB16	0-16
GG2SB25	0-25
GG2SB40	0-40
GG2SB100	0-100
GG2SB160	0-160
GG2SB250	0-250
GG2SB400	0-400
GG2SB700	0-700

## 2 1/2" Face - 1/4" M Thread

Rear Entry



**WIKAI**

Part No.	Bar
GG2SR4	0-4
GG2SR6	0-6
GG2SR10	0-10
GG2SR25	0-25
GG2SR40	0-40
GG2SR100	0-100
GG2SR160	0-160
GG2SR250	0-250
GG2SR400	0-400

With support bracket

## Protector for 2 1/2" Gauges



Part No.
P00600007

## 4" Face - 3/8" M Thread

Bottom Entry



**WIKAI**

Part No.	Bar
GG4SB6	0-6
GG4SB10	0-10
GG4SB16	0-16
GG4SB25	0-25

## 4" Face - 3/8" M Thread

Rear Entry



**WIKAI**

Part No.	Bar
GG4SR6	0-6
GG4SR10	0-10
GG4SR16	0-16

With support bracket

## 6" Face - 1/2" M Thread

Bottom Entry



**WIKAI**

Part No.	Bar
GG6SB10	0-10

## 2" Face - 1/4" M Thread

Rear Entry



**Plastic Case**

Part No.	Bar
293000002	0-6 Bar

## Gauge Isolator



Part No.
8392064

- 1/4" BSPM inlet
- 1/4" BSPF gauge fitting
- Viton diaphragm
- AISI303 Stainless steel body
- Can be filled with glycerine or water
- Maximum pressure 21 Bar