



Low Pressure Swivels.....	278
High Pressure Swivels.....	278 - 279
Mosmatic Swivels.....	280

Available from B&G Cleaning Systems
Call 0808 163 7983

Swivels

Low Pressure Swivels - up to 40 Bar

Banjo Swivels - Polypropylene



Part No.	Threads
9901-SW100	1" F x 1" M
9901-SW150	1 1/2" F x 1 1/2" M
9901-SW200	2" F x 2" M
9901-SW220	2" F x 2" M - Full Port

- Max press 5 Bar
- Teflon® thrust bearing
- Viton seals
- Stainless steel drive stud

Banjo Flanged Swivel - Polypropylene



Part No.	Flanges
9901-MSW220	2" Full Port

- Max press 5 Bar
- Teflon® thrust bearing
- EPDM seals
- Stainless steel drive stud

SW65 Swivel - Brass



Part No.	Threads
30.6480.00	1/2" M x 1/2" F

- Max press 24 Bar
- Max flow 100 Lpm
- Max temp 100°C
- Viton & Buna seals
- Ball bearing swivel



SWIF Swivels - S/Steel



Part No.	Threads
SWIFMF1	1/2" M x 1/2" F

- Max press 30 Bar
- Max flow 40 Lpm
- Max temp 95°C
- Viton seals
- Ball bearing swivel



SW65 Hose Tail Swivel - Brass



Part No.
30.6430.00



- Brass construction
- Max press 24 Bar
- Max flow 100 Lpm
- Max temp 90°C
- 1/2" BSPM x 1/2" Ø Barb



SWIF Hose Tail Swivels - S/Steel



Part No.	Thread x Barb
SWIFB13	1/2" M x 13mm
SWIFB16	1/2" M x 16mm
SWIFB19	1/2" M x 19mm

- Max press 40 Bar
- 316 stainless steel
- Max temp 95°C
- Viton seals



High Pressure Swivels - 100 to 600 Bar

SW5 Swivels - S/Steel or Brass



Part No.	Threads	Material
26.1070.00	1/2" M x 1/2" F	S/Steel
26.1080.00	1/2" M x 1/2" F	Brass



- Max press 200 Bar
- Max flow 160 Lpm
- Max temp 90°C
- Viton o-rings



LR Swivels - Brass



Part No.	Threads
26.1000.00	3/8" M x 3/8" F
26.1000.05	3/8" M x 1/4" F

- Max press 220 Bar
- Max flow 30 Lpm
- Max temp 90°C
- Buna seals

HP Swivels - Brass



Part No.	Threads
4100801005	3/8" M x 3/8" M
4100801006	3/8" M x 1/4" M
4100801007	3/8" M x M22 M

- Max press 220 Bar
- Max flow 30 Lpm
- Max temp 150°C
- Viton seals

HP Swivels - Brass



Part No.	Threads
371702	3/8" M x 3/8" F

- Max press 280 Bar
- Max flow 30 Lpm
- Max temp 150°C
- Viton seals

MR-0 Swivels - Brass

Part No.	Threads
26.1040.00	1/4" M x 1/4" F
26.1050.00	3/8" M x 3/8" F
26.1055.00	1/2" M x 1/2" F

- Max press 250 Bar
- Max flow 40 Lpm
- Max temp 160°C
- Viton seals



HP Swivel - S/Steel

Part No.	Threads
371700	3/8" M x 3/8" F

- Max press 280 Bar
- Max flow 30 Lpm
- Max temp 150°C
- Viton seals



MR-1 Swivels - S/Steel

Part No.	Threads
26.1060.00	1/4" M x 1/4" F
26.1061.00	3/8" M x 3/8" F

- Max press 350 Bar
- Max flow 40 Lpm
- Max temp 160°C
- Viton seals



AGS45 Swivel - S/Steel

Part No.	Threads
22.0435	3/8" F x 3/8" M

- Max press 400 Bar
- Max flow 45 Lpm
- Max temp 160°C
- Stainless steel body



SW600 Swivel - S/Steel

Part No.	Threads
30.5840.00	3/8" M x 3/8" F

- Max press 600 Bar
- Max flow 60 Lpm
- Max temp 100°C
- 30 Rpm max speed
- NBR (Buna) seals



990 90° Swivels - Brass

Part No.	Threads
990-6F6F-B	3/8" F x 3/8" F
990-6F6M-B	3/8" F x 3/8" M

- Max press 100 Bar
- Brass construction
- Max temp 80°C
- Buna N seals



SW5 90° Swivel - S/Steel

Part No.	Threads
26.1078.00	1/2" F x 3/8" F

- Max press 200 Bar
- Max flow 160 Lpm
- Max temp 90°C
- Stainless steel body
- FKM (Viton) seals



SW90 90° Swivels - Brass & S/Steel

Part No.	Threads	Bar	Lpm
26.1300.20	1/4" M x 1/4" F	250	40
26.1300.40	3/8" M x 3/8" F	250	40
26.1320.00	1/2" M x 1/2" F	350	80

- Max flow 80 Lpm - Max press 350 Bar
- Max temp 160°C
- Teflon® & Viton seals
- S/Steel bolt & nickel plated brass body
- 26.1320.00 complete s/steel body



SW90-600 90° Swivel - S/Steel

Part No.	Threads	Bar	Lpm
26.1330.00	1/2" M x 1/2" F	600	80

- Max flow 80 Lpm - Max press 600 Bar
- Max temp 90°C
- Teflon® & Viton seals
- S/Steel body



Mosmatic Swivels

Mosmatic Heavy-Duty Swivels

- Nickel plated brass body
- Triple bearing system
- Stainless steel bearings
- Multiple seal system
- Totally corrosion resistant
- For water, oil, air, pH 3-12

DGL - Triple Bearing Female x Male Thread



Part No.	Female	Male
31.001	1/4" BSP	1/4" BSP
31.003	1/4" BSP	3/8" BSP
31.103	3/8" BSP	3/8" BSP

- Max press 275 Bar
- 30 Rpm max @ 120°C
- 1000 Rpm max @ 30°C

DGL - Triple Bearing Female Thread



Part No.	Female	Female
31.002	1/4" BSP	1/4" BSP

- Max press 275 Bar
- 30 Rpm max @ 120°C
- 1000 Rpm max @ 30°C

DGS - Dual Bearing Female x Male Thread



Part No.	Female	Male
30.003	1/4" BSP	3/8" BSP
30.103	3/8" BSP	3/8" BSP

- Max press 275 Bar
- 30 Rpm max @ 120°C
- 1000 Rpm max @ 30°C

DGK Single Bearing Hose Barb x Thread



Part No.	Thread	Barb
32.031	1/4" BSP	6mm
32.032	1/4" BSP	8mm
32.039	1/4" BSP	10mm
32.131	3/8" BSP	6mm
32.132	3/8" BSP	8mm
32.139	3/8" BSP	10mm

- Max press 275 Bar
- 30 Rpm max @ 120°C
- 1000 Rpm max @ 30°C



WDG - Triple Bearing 90° Swivels

Part No.	Female Thread	Male Thread	Dimension (A)
40.009*	1/4" BSPF	1/4" BSPM Parallel	7mm ID
40.013	3/8" BSPF	3/8" BSPM Tapered	7mm ID
40.112	3/8" BSPF	3/8" BSPM Parallel	10mm ID

- Max press 150 Bar
- Max temp 90°C
- Max speed 30 Rpm
- Easy turning at high pressure
- * Without snap ring

Mosmatic DGG - DGF Triple Heavy-Duty Bulkhead Swivels

- Max press 275 Bar
- 30 Rpm max @ 120°C
- 1000 Rpm max @ 30°C
- Nickel plated brass body
- Triple bearing system
- Stainless steel bearings
- Multiple seal system
- Totally corrosion resistant
- For water, oil, air, pH 3-12



Female thread x Male thread

Part No.	Female	Male
33.001	1/4" BSP	1/4" BSP
33.003	1/4" BSP	3/8" BSP
33.103	3/8" BSP	3/8" BSP



90° M22 Male x Male thread

Part No.	Male	Male
33.553	M22 x 1.5 M	3/8" BSP